

CL408e/412e - CL608e/612e

主要参数:



		CL408e	CL412e		CL608e	CL612e	
打印方式		直热 / 热转印					
打印分辨率		203dpi (8dpmm)		305dpi (12dpmm)	203dpi (8dpmm)	305dpi (12dpmm)	
最大打印范围		W104mm x L1249mm		W104mm x L833mm	W152mm x L1249mm	W165mm x L833mm	
		(W4.1" x L49.2")		(W4.1" x L32.8")	(W6.0" x L49.2")	(W6.5" x L32.8")	
打印速度		50mm - 150mm/sec (2- 6ips)			100mm - 200mm/sec (4- 8ips)		
介质类型		卷筒纸, 模切纸, 连续纸, 吊牌					
介质尺寸		宽度		22 - 128mm (0.86 - 5.0")		47 - 177mm (1.85 - 7.0")	
		长度		6 - 1249mm (0.24-49.2")	6 - 833mm (0.24-32.8")	19 - 1249mm (0.75-49.2")	19 - 833mm (0.75-32.8")
		卷状标签最大长度 : 210M (689"); 卷状标签最大外径 : 218mm (8.6")					
介质厚度		最大 0.25mm					
碳带		宽度		最大 111mm (4.4")		最大 172mm (6.75")	
		长度		最大 450M (1475')		最大 410M (1345')	
		厚度		4.5 micron, 内卷			
感应模式		反射模式 (用于预先打印好黑标的标签)					
		穿透模式 (用于间隙类标签)					
处理器		32-Bit RISC, 118MHz; Flash ROM : 2MB / 4MB (Option); Receive Buffer : 2.95MB (Buffer near full at 2MB)					
接口选择		Serial : RS232C (up to 57.6K bps), RS-422/485; Parallel : IEEE1284 (ECP); USB : Ver. 1.1; LAN : 10/100 Base T; Wireless LAN					
条码		一维码	UPC-A/E, EAN, JAN, CODE 39, CODE 93, CODE 128, UCC/EAN 128, Interleaved 2/5, Industrial 2/5, Matrix 2/5, NW-7, MSI, Postnet, Bookland				
		二维码	QR Code, PDF417, Veri Code, Maxi Code, Data Matrix, RSS-14				
		条码比例	1:2, 1:3, 2:5, User definable bar widths, Programmable heights up to 999 dots				
条码旋转		0°, 90°, 180°, 270°					
字体		内置字体					
		OCR-A 15x22, OCR-B 20x24	OCR-A 22x23, OCR-B 30x36	OCR-A 15x22, OCR-B 20x24	OCR-A 22x23, OCR-B 30x36		
图形支持		SATO Hex/Binary or .PCX Format					
外部接口		Parallel :36-pin Amp; Serial : DB-25; Ext (Acry) : 14-pin Amp					
功能		特性	Status Report, Graphics, Sequential Numbering, Form Overlay Store, Customised Design Character, Font Decoration, Reverse Image,				
			Line Print, Hex Dump Print, Format Store, Outline, Outline Variation, Label Skip, Zero Slash Switchover				
		自检	打印头、打印纸末端、碳带末端、碳带接近末端				
打印头开打、存储卡错误、打印测试、切刀盖打开							
外形尺寸		W271 x D430 x H321mm (W10.7 x D16.9 x H12.6")			W352 x D429 x H298mm (W13.7 x D16.9 x H11.7")		
重量		13Kg (28.6lb.)			19Kg (41.8lb.)		
电源要求		110/220V (+/-10%), 50/60Hz (+/-1%); 待机 : 50W; 运行 : 130W			110/220V (+/-10%), 50/60Hz (+/-1%); 待机 : 50W; 运行 : 210W		
环境要求		运行环境	5-40°C (41-104°F) 无凝结, 15-85% RH				
		储存环境	-5-60°C (23-140°F) 无凝结, Max 90% RH, ESD : 8kV				
认证情况		FCC Class A, U/L, TUV, CE, CSA, CCC					
RFID (选件)		High Frequency (HF) & Ultra High Frequency (UHF)			无		
选件		切刀、旋转切刀、剥离器、内置回卷器、日历、PCMCIA卡			切刀、剥离器、日历、回卷器		

Dongguan Lesain Barcode Co., Ltd.,
Tel:0769-23095998 23095997
Fax:0769-22327189
Website:http://www.lesain.com