

高性能、高速度的条码打印机



GT 系列

选配件



即装即用打印头



三种接口功能



宽大的液晶显示屏



操作按钮



折叠纸打印功能



表现完美的工业型条码打印机

GI 系列是索尼高性能的高速工业型条码打印机。它具备了标贴打印中所有卓越的特点，完全能满足您对业务的严格要求。它的打印速度可达 12 英寸 / 秒，可以说是当今打印速度最快的条码打印机之一。这款机器的外观设计优美加上德国的铝制机身，独一无二的设计在高速打印时仍能保持打印质量。此外，用户可以自行更换打印头，简单便捷，无需任何工具，即装即用，不用怀疑。SATO 是完全满足您对打印需要的引领者。

	CIT108	CIT112	CIT124	
打印方式 分辨率	203dpi (86ppm)	305dpi (126ppm)	609dpi (244ppm)	
最大打印范围	W104mm x L550mm (W4.1" x L59.4") 50mm - 300mm/sec (2+12ips), Default 102mm/sec (4ips)	W104mm x L1500mm (W4.1" x L59.1") Default 76.2mm/sec (3ips)	W104mm x L400mm (W4.1" x L15.7") 50mm - 150mm/sec (2-6ips)	
打印速度				
介质类型				
介质尺寸	标准 切刀 / 剪 / 卷 标签幅	SATO recommended roll paper and finfold, 介纸厚度: 0.06 ~ 0.28mm W22 - 128mm x P6 - 997mm 底纸尺寸: W25 - 131mm x P6 - 400mm W122 - 128mm x K 17 - 397mm 底纸尺寸: W25 - 131mm x P160 - 400mm 最大外径: 265mm (10.43") 最大内径: 128mm (5.07"), 最小 39.5mm (1.55") 最大 450M (1475") 最大 25.4+/-2mm (1") 最大 65mm (3.55") 最大 25.4+/-2mm (1") 内卷 / 外卷		
接口选择	宽度 长度 卷绕方式 外径尺寸 内径尺寸			
感应模式				
处理逻辑		32-Bit RISC / 118MHz, Flash-ROM: 6MB (Main Memory: 4MB, Font: 2MB) Interface Buffer: 2.93MB, RAM:16MB, Cartridge Memory: English - 8MB, Chinese, Korean & Thai - 20MB RS232C, High Speed RS232C, USB (12Mbps - V=1.1 Equivalent), IEEE1284 LAN Wireless LAN, Centronics, RS422/485, MVI LAN 一维码: UPC-A/E, JAN/813, EAN-8/13, CODE 39, 89 & 128, UCC/EAN 128, Interleaved 2/5 (ITF) 工业级 2/5, Matrix 2/5, NW 7, NSI, Bookland, Postnet, RSS-14, Customer Barcode 二维码: QR Code, PDF417, Max Code, Data Matrix ECC200 (Ver2.0), Composite Symbology (Compatible with CC-A/B/C by JPC-A/B/C, JAN/EAN/813, CODE 39, 128 and RSS-14) 12, 13, 2, 5 (自行指定)		
条码识别				
条码比例		字体: Height 1 ~ 12 times, Width 1 ~ 12 times, 条码: L1 - L12 XL, XS, XM, XB, XL, Outline, OCR-A, OCR-B 标准: CG Times (AlphaNumeric / Symbol), CG Triumvirate (AlphaNumeric / Symbol) 可选: 希腊, 韩文, 阿拉伯语, 中文, 日文, 英文 SATO Hex / Binar 或 PCX 格式		
放大比例		0° - 90°, 180°, 270°		
条码旋转				
字体	内部字体 字体类型			
图案支持		Custom Character Storage, Character Correction, Black / White Inversion, Dump List, Format Storage Function Status Return Function, Outline Function Outline Variable Function, Label Skip Function, Graphic Print, Sequential Number Print Line & Box Print, Form Overlay Print		
	特性	Selection of with or without "r" for zero, JIS / Shift JIS Switching Function 标准: 打印头检测, 纸带厚度, 碳带寿命, 碳带剩量可用, 碳带中心误差, 打印测试 可选: 标签耐用测试, Keypil ROM 检查, 切口打开检测, 回卷已用警告, 剩量报警清除 LINE, FEED, FUNCTION, ENTER, CANCEL & Directional Keys		
	自检	状态指示(仁包盖)		
	指示灯	W128 x H64 dots Graphic LCD (带背景灯) PRINT, PITCH, PITCH OFFSET & VOLUIME		
	液晶屏	W271 x D455 x H855mm (W10.7" x D17.8" x H12.0") 约 15kg (待运重量)		
外形尺寸				
重量				
电源	100 ~ 240V (+/-10%), 50 / 60Hz (+/-1%), Idec: 40W, Operation (Peak): 150W (at 30% print density) 0° - 40°C (32° - 104°F) non-condensing, Max 30% - 80% RH 批准不使用于标准磁带 -5° - 60°C (23° - 140°F) non-condensing, Max 30% - 90% RH * 湿度不适用于标准磁带			
环境要求	工作温度 相对湿度	VCCI Class B, EEC level3, 100V~P or more		
噪音测试				
选配件		Carter (Guillotine), Wireless Kit, Simplified Dispenser, Label Near-End Sensor, Dispenser Unit (with Backing Paper Rewinder), Internal Rewinder, External Rewinder RFID Kit & Verifier Mounting Bracket		

GT408e/GT412e/GT424e



**The Standard For Reliable
Barcode Printing**

Dongguan Lesain Barcode Co., Ltd.

Tel: 0769-23095998 23095997

Fax: 0769-22327189

Website: <http://www.lesain.com>