

M-84PRO

主要参数:



The True Industrial Printer

打印方式	直热/热转印		
打印分辨率	203/305/609dpi (8/12/24dppm)可选		
最大打印范围	203 dpi: W104mm x L1249mm (W4.1" x L49.2")		
	305 dpi: W104mm x L835mm (W4.1" x L32.8")		
	609 dpi: W104mm x L356mm (W4.1" x L14")		
打印速度	203 dpi: 2, 4, 6, 8, 10 ips		
	305 dpi: 2, 4, 6, 8 ips		
	609 dpi: 2, 3, 4, 5, 6 ips		
标签类型	模切纸, 折叠纸, 吊牌, 连续纸		
标签尺寸	宽度22mm ~ 125mm (0.87"~ 5.1")		
	长度6mm ~ 356mm (0.24" ~ 14.0")		
磁带	宽度38mm ~ 111mm (1.5" ~ 4.4"), 长度450m (Up to 1475ft), 厚度4.5 micron, 内卷		
感应模式	Adjustable photo-sensor position for die-cut labels & tags, Fixed reflective sensor for use with preprinted I-marks, Continuous forms with "Sensor Not Used" mode		
处理器	32 Bit RISC/133 MHz, Receive Buffer: 2.95MB Flash ROM: 2MB (4MB optional) (buffer near full at 2MB)		
接口选择	Parallel: IEEE 1284 (ECP), Serial: RS-232C (9600 - 57600 Bps)		RS-422/485 (9600 - 57600 Bps)
	LAN (10/100 BaseT)		USB Version 1.1
条码	Elementary: UPC-A/E, EAN, JAN, CODE 39, CODE 93, CODE 128, UCC/EAN 128, Inter-Leaved 2/5		
	Industrial 2/5, Matrix 2/5, NW-7, MSI, Postnet, Bookland		
	2 D: QR Code, PDF417, Maxi Code, Data Matrix		
点阵字体	内置字体:	XU 5x9 (Alphanumeric, symbols)	XS 17x17 (Alphanumeric, symbols)
		XM 24x24 (Alphanumeric, symbols)	XB 48x48 (Alphanumeric, symbols)
		XL 48x48 (Alphanumeric, symbols)	
		OCR-A (15x22/ 203dpi, 22x33/ 305dpi, 44x66/ 609dpi) (Alphanumeric, symbols)	
		OCR-B (20x24/ 203dpi, 30x36/ 305dpi, 60x72/ 609dpi) (Alphanumeric, symbols)	
矢量字体	轮廓字体:	Alphanumeric, symbols	
	光栅字体:	CG Times (Alphanumeric, symbols), CG Triumvirate (Alphanumeric, symbols)	
	字体旋转:	0°, 90°, 180°, 270° rotation in each data	
	字体扩展:	Vertical 1 ~ 12 times, Horizontal 1 ~ 12 times, L1 ~ L12 for barcode	
	基本功能:	Status Report, Graphics (SATO Hex/Binary, bmp file or pcx file), Sequential Numbering, Form Overlay Store, Customized Design Character, Font Decoration, Reverse Image, Line Print, Hex Dump Print, Format Store	
功能		Outline, Outline Variation, Label Skip, Zero Slash Switchover	
	自检:	打印头, 打印纸末端, 打印头打开	
		储存卡错误, 打印测试	
	控制面板:	LCD: 16x 2 line Alphanumeric (with backlight) Switch: LINE, FEED	
		LED: ERROR, POWER, ONLINE DIP Switch: 2 sets	
		VR: PRINT, OFFSET, PITCH	
	VR调节:	Print Position Adjustments, Cutting/Dispensing/ Tear OFF Position Adjustment, Print Darkness Adjustment	
图形支持	SATO Hex/Binary BMP or PCX Format		
外部接口	Parallel: 36-pin Amp Serial: DB-25 Ext (Accy): 14-pin Amp		
外形尺寸	W265mm x D435mm x H335mm (W10.4" x D17.1" x H13.2")		
重量	18.5kg (40.7 lb.)		
电源要求	110 - 115V (+/-10%), 220V (+/-10%), 50/60 Hz (+/-1%) Idle: 24VA/16W Operation: 190VA/130W		
环境要求	运行: 5 ~ 40°C (41 ~ 104°F) 无凝露, 30 - 80% 存储: -5 ~ 60°C (23 ~ 140°F) 无凝露, 30 - 90%		
认证情况	FCC Class A, UL, TUV, CE, CSA, CCC		
选件	Label Cutter, Label Dispenser, Rewinder, Calendar ROM, PCMCIA Add-On Memory		
	4MB Optional Memory PCB, Serial Bus/Ethernet 10/100 Base T/Coax/Twinax Interface		

Dongguan Lesain Barcode Co., Ltd.,

Tel:0769-23095998 23095997

Fax:0769-22327189

Website:<http://www.lesain.com>